

# GLENN COUNTY

## Planning & Community Development Services Agency

225 N. Tehama St  
Willows, CA 95988  
530.934.6546  
[www.countyofglenn.net](http://www.countyofglenn.net)



## POOL PERMIT PLOT PLAN AND SUBMITTAL REQUIREMENTS

### SHOW FOLLOWING ITEMS ON PLOT PLAN:

1. Location of the proposed pool with distances from the property lines.
2. Locations of existing structures with distances from the pool.
3. Location of the septic tank and leach lines with distances from pool.
4. Location and description of the barriers including locations of all gates or doors must be documented on plans. **Two** barriers are now required by Senate Bill No. 442. (attached)
5. Location of the backflow-prevention device if there will be a permanent connection to the premises water system.
6. Location of the electrical panel which will supply the pool equipment.
7. Location of the required GFI receptacle 6' – 20' from the pool. This must be **inside the barrier**.
8. If the pool will be heated, the location of the heater and it's input in BTU's.
9. Show North directional arrow.
10. Note how anti-entrapment device requirement will be met (provide spec).
11. Show how equipotential grid follows perimeter of pool (N/A for fiberglass pools).

### SUBMIT FOLLOWING ITEMS FOR REVIEW/ APPROVAL

1. Completed Building Permit Application
2. Plot Plan
3. Engineered Pool Plans and Structural Calcs as required
4. Provide Contract Price/ Construction Value



---

## **SWIMMING POOL INSPECTIONS REQUIRED**

1. **PRE-GUNITE:** to check the setbacks and clearances; inspect the steel/rebar installation which will include all grounding, light niche, rough plumbing, and water pressure test (minimum 60 lbs. for 15 minutes or working pressure). **Enclosure to remain in place.**
2. **PRE-DECK:** After Gunite, Inspector will conduct the exterior deck slab inspection to include equipotential grid grounding system of the slab steel, pool accessories, and all metal parts within 5' of the pool.
3. **FINAL:** This inspection will include approval of all barriers (i.e., alarms, fencing, gates or doors); electrical subpanel, GFCI receptacle, and if pool is heated, the heater equipment; and backflow prevention device (if there will be a permanent connection to the premises water system).

NOTE: All inspections are scheduled through the Glenn County  
Inspection Request Line: (530) 934-8447.

---



[Up^](#) [Add To My Favorites](#)

**HEALTH AND SAFETY CODE - HSC**

**DIVISION 104. ENVIRONMENTAL HEALTH [106500 - 119406]** ( *Division 104 added by Stats. 1995, Ch. 415, Sec. 6.*  )

**PART 10. RECREATIONAL SAFETY [115725 - 116095]** ( *Part 10 added by Stats. 1995, Ch. 415, Sec. 6.*  )

**CHAPTER 5. Safe Recreational Water Use [115825 - 116090]** ( *Chapter 5 added by Stats. 1995, Ch. 415, Sec. 6.*  )

**ARTICLE 2.5. The Swimming Pool Safety Act [115920 - 115929]** ( *Article 2.5 added by Stats. 1996, Ch. 925, Sec. 3.5.*  )

**115920.** This act shall be known and may be cited as the Swimming Pool Safety Act.

( *Added by Stats. 1996, Ch. 925, Sec. 3.5. Effective January 1, 1997.* )

**115921.** As used in this article the following terms have the following meanings:

(a) "Swimming pool" or "pool" means any structure intended for swimming or recreational bathing that contains water over 18 inches deep. "Swimming pool" includes in-ground and aboveground structures and includes, but is not limited to, hot tubs, spas, portable spas, and nonportable wading pools.

(b) "Public swimming pool" means a swimming pool operated for the use of the general public with or without charge, or for the use of the members and guests of a private club. Public swimming pool does not include a swimming pool located on the grounds of a private single-family home.

(c) "Enclosure" means a fence, wall, or other barrier that isolates a swimming pool from access to the home.

(d) "Approved safety pool cover" means a manually or power-operated safety pool cover that meets all of the performance standards of the American Society for Testing and Materials (ASTM), in compliance with standard F1346-91.

(e) "Exit alarms" means devices that make audible, continuous alarm sounds when any door or window, that permits access from the residence to the pool area that is without any intervening enclosure, is opened or is left ajar. Exit alarms may be battery operated or may be connected to the electrical wiring of the building.

(f) "ANSI/APSP performance standard" means a standard that is accredited by the American National Standards Institute (ANSI) and published by the Association of Pool and Spa Professionals (APSP).

(g) "Suction outlet" means a fitting or fixture typically located at the bottom or on the sides of a swimming pool that conducts water to a recirculating pump.

( *Amended by Stats. 2012, Ch. 679, Sec. 1. (AB 2114) Effective January 1, 2013.* )

**115922.** (a) Except as provided in Section 115925, **when a building permit is issued for the construction of a new swimming pool or spa or the remodeling of an existing swimming pool or spa at a private single-family home, the respective swimming pool or spa shall be equipped with at least two of the following seven drowning prevention safety features:**

(1) An enclosure that meets the requirements of Section 115923 and isolates the swimming pool or spa from the private single-family home.

(2) Removable mesh fencing that meets American Society for Testing and Materials (ASTM) Specifications F2286 standards in conjunction with a gate that is self-closing and self-latching and can accommodate a key lockable device.

(3) An approved safety pool cover, as defined in subdivision (d) of Section 115921.

(4) Exit alarms on the private single-family home's doors that provide direct access to the swimming pool or spa. The exit alarm may cause either an alarm noise or a verbal warning, such as a repeating notification that "the door to the pool is open."

(5) A self-closing, self-latching device with a release mechanism placed no lower than 54 inches above the floor on the private single-family home's doors providing direct access to the swimming pool or spa.

(6) An alarm that, when placed in a swimming pool or spa, will sound upon detection of accidental or unauthorized entrance into the water. The alarm shall meet and be independently certified to the ASTM Standard F2208 "Standard Safety Specification for Residential Pool Alarms," which includes surface motion, pressure, sonar, laser, and infrared type alarms. A swimming protection alarm feature designed for individual use, including an alarm attached to a child that sounds when the child exceeds a certain distance or becomes submerged in water, is not a qualifying drowning prevention safety feature.

(7) Other means of protection, if the degree of protection afforded is equal to or greater than that afforded by any of the features set forth above and has been independently verified by an approved testing laboratory as meeting standards for those features established by the ASTM or the American Society of Mechanical Engineers (ASME).

(b) Before the issuance of a final approval for the completion of permitted construction or remodeling work, the local building code official shall inspect the drowning safety prevention features required by this section and, if no violations are found, shall give final approval.

*(Amended by Stats. 2017, Ch. 670, Sec. 4. (SB 442) Effective January 1, 2018.)*

**115923.** An enclosure shall have all of the following characteristics:

(a) Any access gates through the enclosure open away from the swimming pool, and are self-closing with a self-latching device placed no lower than 60 inches above the ground.

(b) A minimum height of 60 inches.

(c) A maximum vertical clearance from the ground to the bottom of the enclosure of two inches.

(d) Gaps or voids, if any, do not allow passage of a sphere equal to or greater than four inches in diameter.

(e) An outside surface free of protrusions, cavities, or other physical characteristics that would serve as handholds or footholds that could enable a child below the age of five years to climb over.

*(Added by Stats. 1996, Ch. 925, Sec. 3.5. Effective January 1, 1997.)*

**115924.** (a) Any person entering into an agreement to build a swimming pool or spa, or to engage in permitted work on a pool or spa covered by this article, shall give the consumer notice of the requirements of this article.

(b) Pursuant to existing law, the Department of Health Services shall have available on the department's Web site, commencing January 1, 2007, approved pool safety information available for consumers to download. Pool contractors are encouraged to share this information with consumers regarding the potential dangers a pool or spa poses to toddlers. Additionally, pool contractors may provide the consumer with swimming pool safety materials produced from organizations such as the United States Consumer Product Safety Commission, Drowning Prevention Foundation, California Coalition for Children's Safety & Health, Safe Kids Worldwide, Association of Pool and Spa Professionals, or the American Academy of Pediatrics.

*(Amended by Stats. 2006, Ch. 478, Sec. 3. Effective January 1, 2007.)*

**115925.** The requirements of this article do not apply to any of the following:

(a) Public swimming pools.

(b) Hot tubs or spas with locking safety covers that comply with the American Society for Testing and Materials (ASTM F1346).

(c) An apartment complex, or any residential setting other than a single-family home.

*(Amended by Stats. 2017, Ch. 670, Sec. 5. (SB 442) Effective January 1, 2018.)*

**115926.** This article does not apply to any facility regulated by the State Department of Social Services even if the facility is also used as the private residence of the operator. Pool safety in those facilities shall be regulated pursuant to regulations adopted therefor by the State Department of Social Services.

*(Added by Stats. 1996, Ch. 925, Sec. 3.5. Effective January 1, 1997.)*

**115927.** Notwithstanding any other provision of law, this article shall not be subject to further modification or interpretation by any regulatory agency of the state, this authority being reserved exclusively to local jurisdictions, as provided for in paragraph (7) of subdivision (a) of Section 115922 and subdivision (c) of Section 115925.

*(Amended by Stats. 2018, Ch. 957, Sec. 13. (SB 1078) Effective January 1, 2019.)*

**115928.** Whenever a building permit is issued for the construction of a new swimming pool or spa, the pool or spa shall meet all of the following requirements:

(a) (1) The suction outlets of the pool or spa for which the permit is issued shall be equipped to provide circulation throughout the pool or spa as prescribed in paragraphs (2) and (3).

(2) The swimming pool or spa shall either have at least two circulation suction outlets per pump that shall be hydraulically balanced and symmetrically plumbed through one or more "T" fittings, and that are separated by a distance of at least three feet in any dimension between the suction outlets, or be designed to use alternatives to suction outlets, including, but not limited to, skimmers or perimeter overflow systems to conduct water to the recirculation pump.

(3) The circulation system shall have the capacity to provide a complete turnover of pool water, as specified in Section 3124B of Chapter 31B of the California Building Standards Code (Title 24 of the California Code of Regulations).

(b) Suction outlets shall be covered with antientrapment grates, as specified in the ANSI/APSP-16 performance standard or successor standard designated by the federal Consumer Product Safety Commission, that cannot be removed except with the use of tools. Slots or openings in the grates or similar protective devices shall be of a shape, area, and arrangement that would prevent physical entrapment and would not pose any suction hazard to bathers.

(c) Any backup safety system that an owner of a new swimming pool or spa may choose to install in addition to the requirements set forth in subdivisions (a) and (b) shall meet the standards as published in the document, "Guidelines for Entrapment Hazards: Making Pools and Spas Safer," Publication Number 363, March 2005, United States Consumer Product Safety Commission.

*(Amended by Stats. 2012, Ch. 679, Sec. 2. (AB 2114) Effective January 1, 2013.)*

**115928.5.** Whenever a building permit is issued for the remodel or modification of an existing swimming pool, toddler pool, or spa, the permit shall require that the suction outlet or suction outlets of the existing swimming pool, toddler pool, or spa be upgraded so as to be equipped with antientrapment grates, as specified in the ANSI/APSP-16 performance standard or a successor standard designated by the federal Consumer Product Safety Commission.

*(Amended by Stats. 2012, Ch. 679, Sec. 3. (AB 2114) Effective January 1, 2013.)*

**115929.** (a) The Legislature encourages a private entity, in consultation with the Epidemiology and Prevention for Injury Control Branch of the department, to produce an informative brochure or booklet, for consumer use, explaining the child drowning hazards of, possible safety measures for, and appropriate drowning hazard prevention measures for, home swimming pools and spas, and to donate the document to the department.

(b) The Legislature encourages the private entity to use existing documents from the United States Consumer Product Safety Commission on pool safety.

(c) If a private entity produces the document described in subdivisions (a) and (b) and donates it to the department, the department shall review and approve the brochure or booklet.

(d) Upon approval of the document by the department, the document shall become the property of the state and a part of the public domain. The department shall place the document on its Web site in a format that is readily available for downloading and for publication. The department shall review the document in a timely and prudent fashion and shall complete the review within 18 months of receipt of the document from a private entity.

*(Added by Stats. 2003, Ch. 422, Sec. 3. Effective January 1, 2004.)*